

41510

PCD Fresa Micro Elicoidale



Materiale

Vc

Senza
rivestimentoAcciaio < 700 N/mm²

-

-

Acciaio > 700 N/mm²

-

-

Acciaio inox

-

-

Ghisa

-

-

Rame

350

■

Ottone - Bronzo

500

■

Alluminio

1000

■

Oro - argento

300

■

Platino - Palladio

130

■

Superleghe

-

-

Titanio

-

-

Compositi

200

□

non adatto - adatto □ moltoadatto ■

Brut uniquement
Raw only - Nur rohe
Solo grezzo

Tolleranze

D₁ < 1mm . 0/-0.01D₁ > 1mm . 0/-0.02

D: h5

PCD

Z2-3

8-10°

λ 30°

ap=0.15xd₁

ae=0.03xd₁

ap=1xd₁

Art. n°	d1	Pbiso	D	L	Z
41510d0.20	0.20	0.20	3	38	2
41510d0.30	0.30	0.30	3	38	2
41510d0.40	0.40	0.40	3	38	2
41510d0.50	0.50	0.50	3	38	3
41510d0.60	0.60	0.60	3	38	3
41510d0.70	0.70	0.70	3	38	3
41510d0.80	0.80	0.80	3	38	3
41510d0.90	0.90	0.90	3	38	3
41510d1.00	1.00	1.00	3	38	3
41510d1.10	1.10	1.10	3	38	3
41510d1.20	1.20	1.20	3	38	3
41510d1.30	1.30	1.30	3	38	3
41510d1.40	1.40	1.40	3	38	3
41510d1.50	1.50	1.50	3	38	3

Opzioni
(vedi pagina 000)

7015
≤ Ø6

MCU
≤ Ø3

Altre dimensioni a richiesta